

OnSite™ Wall Racks

Compact, full-featured wall mountings
for your rack-based equipment

Key Features

- Capacity of five, ten, or fifteen rack units
- Greatly reduces wall-space requirements
- Efficiently manages fiber and copper cables
- Swing-out adapters for rear access
- Incredibly strong, but light in weight
- Simple to install (no assembly required)



Rack-and-Stack on a Wall or Backboard

OnSite wall racks solve a growing problem with delivery of communication services at business locations: Where to install all of that chassis-based equipment? Our multi-position racks provide carrier-strength support for standard 19" and 23" chassis in far less space than flat mounting or floor racks. Combined with efficient cable management accessories and swing-out options, each model is a great all-in-one solution for stacked chassis applications.

Carrier-class Construction

These welded wall racks require no assembly and are light enough for a single technician to easily install. The 5U models support up to 100 pounds of equipment, and 10U/15U models support up to 200 pounds, all while meeting Zone 4 earthquake requirements. Built-in bus bars with dual-screw grounding are included on all versions.

Cable Management Options

A clean installation makes the job complete! Available cable management accessories are easy to install and allow each unit to be tailored to as needed. For rear access applications, 19" models can be installed with wall-mounted adapters that allow racks to swing out a full 90 degrees.

Product Specifications

Wall Racks



| Model # | Description | Height | Width | Depth | Weight | Load Capacity | Ground Points |
|----------|---------------------------------|--------|-------|-------|---------|---------------|---------------|
| WR-5UI2 | 5U wall rack for 19" equipment | 11.0" | 22.7" | 12.6" | 10.2 lb | 100 lb | 6 pairs |
| WR-10U | 10U wall rack for 19" equipment | 19.3" | 22.7" | 12.6" | 14.0 lb | 200 lb | 8 pairs |
| WR-10U23 | 10U wall rack for 23" equipment | 19.3" | 26.7" | 12.6" | 14.8 lb | 200 lb | 8 pairs |
| WR-15U | 15U wall rack for 19" equipment | 28.0" | 22.7" | 12.6" | 18.0 lb | 200 lb | 10 pairs |
| WR-15U23 | 15U wall rack for 23" equipment | 28.0" | 26.7" | 12.6" | 19.4 lb | 200 lb | 10 pairs |

(All models meet Telcordia NEBS compliance requirements, including Zone 4 seismic.)

Swing-Out Adapters



| Model # | Description | Height | Width | Depth | Weight | Supported models |
|-----------|---|--------|-------|-------|---------|--------------------|
| SOA-5U | Swing-out adapter for 19" 5U racks | 10.5" | 26.5" | 4.0" | 13.0 lb | WR-5UI2 |
| SOA-10U | Swing-out adapter for 19" 10U and 15U racks | 19.5" | 26.5" | 4.0" | 17.4 lb | WR-10U, WR-15U |
| SOA-10U23 | Swing-out adapter for 23" 10U and 15U racks | 19.5" | 30.5" | 4.0" | 19.4 lb | WR-10U23, WR-15U23 |

(All models meet Telcordia NEBS compliance requirements, including Zone 4 seismic.)

Accessories

Model#: CG-5

Model#: SPL-4H



| Model # | Description |
|-------------|---|
| CG-5 | Side-mounted cable guides with covers; package of 5 |
| SPL-4H | Side-mounted plate with 2 split cable take-up reels |
| REB-3U3 | Pair of 3U/3" rack extension brackets |
| REB-5U3 | Pair of 5U/3" rack extension brackets |
| CMB-1 | Front-mounted cable management bar for 19" racks |
| DRNG-U-1 | Front-mounted D-ring for all racks |
| S03-1224108 | #12-24 x 1/2" screws for rack-mount equipment; package of 100 |